SAP Note

Close

1135105 - Printer Vendor Wizard Note: Toshiba TEC

Version 34 **Validity:** 12.07.2016 - active **Language** English (Master) **Preview**

Header Data

Release Status	For Checking (Target Status: Released for Customer)
Component	BC-CCM-PRN-PVP-TT SAP Printer Vendor Programm: Toshiba TEC
Other Components	BC-CCM-PRN-DVM Druckeradministration
Priority	Recommendations / Additional Info
Responsible	Chikahiro Saegusa (C5184583)
Processor	Parvathy S (I061455)
Created By	Dr. Christian Hansen (D023980)
Category	Special development
Relevant for Translation	Yes

Symptom

The company Toshiba TEC is member of the SAP Printer Vendor program and offers within this program support for the printer model / device type pairs listed below.

For general information about the SAP Printer Vendor program please check note 1130927.

The printer model / device type combinations are visible in the newest data version of the "device type wizard". Please read note 1036961 for a description how to use the device type wizard and how to select one of the combinations shown below.

The device types are delivered as attachments to this note. Please download the files and proceed with the installation as described in note 1103422.

Certain features of the device types become active only with the following releases and support package levels:

Additional print options: (see note 1049778)
SAP_BASIS 6.20 SP63 and higher
SAP_BASIS 6.40 SP21 and higher
SAP_BASIS 7.00 SP14 and higher
SAP_BASIS 7.10 standard

Other Terms

SPAD , device type , SAP Printer Vendor program

Reason and Prerequisites

[Enter your Reason and Prerequisites here...]

Solution

Supported Printer model/ device type combinations:

ID / Printer model / device type / character set / version
[001] / e-STUDIO6530C Series / TT6CI11.PRI / ISO1 / 1.1
[002] / e-STUDIO4520C Series / TT4EI11.PRI / ISO1 / 1.1
[003] / e-STUDIO455 Series / TT4PI11.PRI / ISO1 / 1.1
[004] / e-STUDIO855 Series / TT8NI11.PRI / ISO1 / 1.1
[005] / e-STUDIO6530C Series / TT6CI21.PRI / ISO2 / 1.1
[006] / e-STUDIO4520C Series / TT4EI21.PRI / ISO2 / 1.1
[007] / e-STUDIO455 Series / TT4PI21.PRI / ISO2 / 1.1
[008] / e-STUDIO855 Series / TT8NI21.PRI / ISO2 / 1.1
[009] / e-STUDIO262CP 263CS / TTC2I11.PRI / ISO1 / 1
[010] / e-STUDIO382P 332P / TTM3I11.PRI / ISO1 / 1
[011] / e-STUDIO223CS 222CS 222CP / TTD2I11.PRI / ISO1 / 1
[012] / e-STUDIO6550C Series / TT6DI11.PRI / ISO1 / 1
[013] / e-STUDIO4540C Series / TT4FI11.PRI / ISO1 / 1
[014] / e-STUDIO6550C Series / TT6DI21.PRI / ISO2 / 1
[015] / e-STUDIO4540C Series / TT4FI21.PRI / ISO2 / 1
[016] / e-STUDIO263CS / TTD2JA1.PRI / JAPANESE / 1
[017] / e-STUDIO456 Series / TT4QI11.PRI / ISO1 / 1
[018] / e-STUDIO856 Series / TT8OI11.PRI / ISO1 / 1
[019] / e-STUDIO456 Series / TT4QI21.PRI / ISO2 / 1
[020] / e-STUDIO856 Series / TT8OI21.PRI / ISO2 / 1
[021] / e-STUDIO332S / TTN3I11.PRI / ISO1,2,5,7,9 / 1
[022] / e-STUDIO403S / TTM4I11.PRI / ISO1,2,5,7,9 / 1
[023] / e-STUDIO2550C Series / TT2CI11.PRI / ISO1 / 1
[024] / e-STUDIO2550C Series / TT2CI21.PRI / ISO2 / 1
[025] / e-STUDIO224CS / TTE2U81.PRI / ISO1,2,5,7,9 / 1
[026] / e-STUDIO263CP 264CS / TTF2U81.PRI / ISO1,2,5,7,9 / 1
[027] / e-STUDIO383P / TTO3U81.PRI / ISO1,2,5,7,9 / 1
[028] / e-STUDIO306LP Series / TT3MI11.PRI / ISO1 / 1
[029] / e-STUDIO306LP Series / TT3MI21.PRI / ISO2 / 1
[030] / e-STUDIO407CS Series / TT4GI11.PRI / ISO1 / 1
[031] / e-STUDIO407CS Series / TT4GI21.PRI / ISO2 / 1
[032] / e-STUDIO527S Series / TT5MI11.PRI / ISO1 / 1
[033] / e-STUDIO527S Series / TT5MI21.PRI / ISO2 / 1
[034] / e-STUDIO307LP Series / TT3MI11.PRI / ISO1 / 1
[035] / e-STUDIO307LP Series / TT3MI21.PRI / ISO2 / 1
[036] / e-STUDIO385S / TTP3I11.PRI / ISO1 / 1
[037] / e-STUDIO385P / TTQ3I11.PRI / ISO1 / 1
[038] / e-STUDIO305CS / TTC3I11.PRI / ISO1 / 1
[039] / e-STUDIO305CP / TTD3I11.PRI / ISO1 / 1
[040] / e-STUDIO525P / TTM5I11.PRI / ISO1 / 1
[041] / e-STUDIO306CS / TTE3I11.PRI / ISO1 / 1
[042] / e-STUDIO425S / TTN4I11.PRI / ISO1 / 1
[043] / e-STUDIO5005AC Series / TT5CI11.PRI / ISO1 / 1
[044] / e-STUDIO5005AC Series / TT5CI21.PRI / ISO2 / 1
[045] / e-STUDIO5008A Series / TT5NI11.PRI / ISO1 / 1
[046] / e-STUDIO5008A Series / TT5NI21.PRI / ISO2 / 1
[047] / e-STUDIO7506AC Series / TT7CI11.PRI / ISO1 / 1
[048] / e-STUDIO7506AC Series / TT7CI21.PRI / ISO2 / 1
[049] / e-STUDIO8508A Series / TT8PI11.PRI / ISO1 / 1
[050] / e-STUDIO8508A Series / TT8PI21.PRI / ISO2 / 1

* e-STUDIO6530C Series: e-STUDIO5520C/6520C/6530C
* e-STUDIO4520C Series: e-STUDIO2020C/2330C/2820C/2830C/
3520C/3530C/4520C/3520Ci
* e-STUDIO455 Series: e-STUDIO205L/255/305/355/455/

305S/355S/455S/305SD/355SD/455SD
* e-STUDIO855 Sreies: e-STUDIO555/655/755/855
* e-STUDIO6550C Series: e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C
* e-STUDIO4540C Series: e-STUDIO2040C/2540C/3040C/3540C/4540C
* e-STUDIO456 Series: e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507
* e-STUDIO856 Sreies: e-STUDIO556/656/756/856/557/657/757/857
* e-STUDIO2550C Series: e-STUDIO2050C/2550C/
2555C/3055C/3555C/4555C/5055C
* e-STUDIO306LP Series: Loops-LP30/e-STUDIO306LP
* e-STUDIO407CS Series: e-STUDIO287CS/347CS/407CS
* e-STUDIO527S Series: e-STUDIO527S/477S
* e-STUDIO307LP Series: Loops-LP301/e-STUDIO307LP
* e-STUDIO5005AC Series: e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC
* e-STUDIO5008A Series: e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A
* e-STUDIO7506AC Series: e-STUDIO5506AC/6506AC/7506AC
* e-STUDIO8508A Series: e-STUDIO5508A/6508A/7508A/8508A

* ISO1: Latin 1, ISO2: Latin 2.
* ISO5: Cyrillic, ISO7: Greek, ISO9: Turkey.

Note: Hold Print
To use the "Hold Print" function in e-STUDIO5520C/6520C/6530C, the system ROM version should be T430SY0*200 or later.
To use the "Hold Print" function in e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci, the system ROM version should be T450SY0*201 or later.
The device type files [001] TT6CI11.PRI, [002] TT4EI11.PRI, [005] TT6CI21.PRI, [006] TT4EI21.PRI do not contain an entry for "Hold Print". If you want to use the "Hold Print" function, please follow the instructions below:
- In "Printer Initialization" screen, find a line @PJL COMMENT DSSC PRINT PRINTMODE=NORMAL and change the value from "NORMAL" to "HOLD".

Label Printers
The device types listed below can be used to convert a label created using Smart Forms into the ZPL II printer control language and to print it on the Z-Mode enabled Toshiba TEC label printers. In this case, the label is designed in Smart Forms and not by an external program for designing labels. (See SAP Note 168368 for Smart Forms).

ID / Printer model / Device type / Character set / Driver
[L001] / B-EX 203dpi / TTLZBI12.PRI / ISO1 / LZPL
[L002] / B-EX 300dpi / TTLZBI13.PRI / ISO1 / LZPL
[L003] / B-EX 600dpi / TTLZBI16.PRI / ISO1 / LZPL
[L004]./.B-SA 203dpi...../.TTLZBI12.PRI..../.ISO1...../.LZPL
[L005]./.B-SA 300dpi...../.TTLZBI13.PRI..../.ISO1...../.LZPL
[L006]./.B-SX6T...../.TTLZBI13.PRI..../.ISO1...../.LZPL

* B-EX 203dpi: B-EX4T2-G, B-EX4T1-G, B-EX4D2-G
* B-EX 300dpi: B-EX4T2-T, B-EX4T1-T, B-EX4D2-T
* B-EX 600dpi: B-EX4T2-H
* B-SA 203dpi: B-SA4TM-G, B-SA4TP-G
* B-SA 300dpi: B-SA4TM-T, B-SA4TP-T
* B-EX4T2 print heads are Flat-type with Paper aligned to Left and B-EX4T1 print heads are Near-edge with Paper aligned to the Center.

Note:
1) To use LZPL driver, read SAP Note 750002 for release level requirements and restrictions.
2) When printing a Smart Form, user is adviced to examine the actual printout of the form from

the printer, rather than just relying on the print preview image.
3) Following cases may occur while printing Smart Forms:
a) Print position and font size are slightly different.
b) Toshiba TEC's printer specifications apply, for example the memory capacity and the number of fields.
c) If an object is placed outside the print area or the print start position of an object is placed within the print area but the end position is outside the print area, the part beyond the print area will be printed starting on the left end of the new line.

Details:

<Supported features>
[001] e-STUDIO5520C/6520C/6530C TT6CI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[002] e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci TT4EI11.PRI
[PDL]: PCL

[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[003] e-STUDIO205L/255/305/355/455/305S/355S/455S/305SD/355SD/455SD TT4PI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[004] e-STUDIO555/655/755/855 TT8NI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

[005] e-STUDIO5520C/6520C/6530C TT6CI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape

Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[006] e-STUDIO2020C/2330C/2820C/2830C/3520C/3530C/4520C/3520Ci TT4EI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart

Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[007] e-STUDIO205L/255/305/355/455/305S/355S/455S/305SD/355SD/455SD TT4PI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[008] e-STUDIO555/655/755/855 TT8NI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort

Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

[009] e-STUDIO262CP/263CS TTC2I11.PRI
[Supported languages]: ISO1 (Latin 1)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Print in color:
Password protection:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[010] e-STUDIO382P/332P TTM3I11.PRI
[Supported languages]: ISO1(Latin 1)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[011] e-STUDIO223CS/222CS/222CP TTD2I11.PRI
[Supported languages]: ISO1(Latin 1)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Print in color:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[012] e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C TT6DI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[013] e-STUDIO2040C/2540C/3040C/3540C/4540C TT4FI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[014] e-STUDIO5540C/6540C/6550C/5560C/6560C/6570C TT6DI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)

[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[015] e-STUDIO2040C/2540C/3040C/3540C/4540C TT4FI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: Tray 1, *Tray 2, Inner Tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[016] e-STUDIO263CS TTD2JA1.PRI
[Supported languages]: Japanese (SJIS)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
[Printer Type]: Color LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Print in color:
Password protection:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[017] e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507 TT4QI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[018] e-STUDIO556/656/756/856/557/657/757/857 TT8OI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

[019] e-STUDIO206L/256/306/356/456/207L/257/307/357/457/507 TT4QI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL

[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[020] e-STUDIO556/656/756/856/557/657/757/857 TT8O21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

[021] e-STUDIO332S TTN3I11.PRI
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome LED Printer
[POSS (Additional print options)]
Input trays:

Double-sided Printing:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[022] e-STUDIO403S TTM4I11.PRI
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Password protection:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[023] e-STUDIO2050C/2550C/2555C/3055C/3555C/4555C/5055C TT2CI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom,

Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[024] e-STUDIO2050C/2550C/2555C/3055C/3555C/4555C/5055C TT2CI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04

Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[025] e-STUDIO224CS TTE2U81.PRI
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Print in color:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[026] e-STUDIO263CP/264CS TTF2U81.PRI
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
Print in color:
Password protection:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[027] e-STUDIO383P TTO3U81.PRI
[Supported languages]: Latin1 (ISO1), Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
[PDL]: PCL
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome LED Printer
[POSS (Additional print options)]
Input trays:
Double-sided Printing:
[Printer-resident bar code]:
-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
[SNMP Job status feedback]:
- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

[028] Loops-LP30/e-STUDIO306LP TT3MI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4
Output tray: *Inner Tray, Job Separator Upper, Job Separator Lower
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Distinguish Thin Line: Yes

[029] Loops-LP30/e-STUDIO306LP TT3MI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No

[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4
Output tray: *Inner Tray, Job Separator Upper, Job Separator Lower
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Distinguish Thin Line: Yes

[030] e-STUDIO287CS/347CS/407CS TT4GI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: *Tray 1, Inner Tray
Stapling: *None, Top Left, Top Right
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[031] e-STUDIO287CS/347CS/407CS TT4GI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: *Tray 1, Inner Tray
Stapling: *None, Top Left, Top Right
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[032] e-STUDIO527S/477S TT5MI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4

Output tray: *Tray 1, Inner Tray
Stapling: *None, Top Left, Top Right
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[033] e-STUDIO527S/477S TT5MI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A4, DIN A5, LETTER, EXECUTIVE, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: *Tray 1, Inner Tray
Stapling: *None, Top Left, Top Right
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[034] Loops-LP301/e-STUDIO307LP TT3MI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4
Output tray: *Inner Tray, Job Separator Upper, Job Separator Lower
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

Distinguish Thin Line: Yes

[035] Loops-LP301/e-STUDIO307LP TT3MI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: No
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, Drawer 3, Drawer 4
Output tray: *Inner Tray, Job Separator Upper, Job Separator Lower
User login: Yes
Department code: Yes (5 digit numbers)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Distinguish Thin Line: Yes

[036] e-STUDIO385S TTP3I11.PRI
[PDL]: PCL5
[Scripts/Languages]: ISO1 (Latin 1)
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome laser printer
[POSS (Additional print options)]
Input trays selection:
Output tray selection:
Double-sided Printing:
User password:
Vendor-defined (2-up printing):

[037] e-studio385P TTQ3I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)
[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome laser printer
[POSS (Additional print options)]
Input trays selection:
Output tray selection:
Double-sided Printing:
Vendor-defined (2-up printing):

[038] e-STUDIO305CS TTC3I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)

[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color laser printer
[POSS (Additional print options)]
Input tray selection:
Output tray selection:
Print in Color/Mono:
Double-sided Printing:
User password:
Vendor-defined (2-up printing):

[039] e-STUDIO305CP TTD3I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)
[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Color laser printer
[POSS (Additional print options)]
Input tray selection:
Output tray selection:
Print in Color/Mono:
Double-sided Printing:
User password:
Vendor-defined (2-up printing):

[040] e-STUDIO525P TTM5I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)
[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome laser printer
[POSS (Additional print options)]
Input trays selection:
Output trays selection:
Double-sided Printing:
Staple option:
Hole punch option:
User password:
Vendor-defined (2-up printing):

[041] e-STUDIO306CS TTE3I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)
[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome laser printer
[POSS (Additional print options)]
Input trays selection:
Output trays selection:
Double-sided Printing:
Staple option:
Hole punch option:
User password:
Vendor-defined (2-up printing):

[042] e-STUDIO425S TTN4I11.PRI
[Scripts/Languages]: ISO1 (Latin 1)
[PDL]: PCL5
[Paper sizes]: A4,A5, LETTER, EXECUTIVE, LEGAL
[Printer Type]: Monochrome laser printer
[POSS (Additional print options)]
Input trays selection:
Output trays selection:
Double-sided Printing:
Staple option:
Hole punch option:
User password:
Vendor-defined (2-up printing):

[043] e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC
TT5CI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes

Black overprint: Yes

[044] e-STUDIO2000AC/2500AC/2005AC/2505AC/3005AC/3505AC/4505AC/5005AC TT5CI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[045] e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A TT5NI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes

[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[046] e-STUDIO2008A/2508A/3008A/3508A/4508A/5008A TT5NI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4
Output tray: Tray 1, *Tray 2, Inner Tray, Job Separator Upper, Job Separator Lower
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-999
Booklet: Yes
Font pitch: Yes

[047] e-STUDIO5506AC/6506AC/7506AC TT7CI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No

[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[048] e-STUDIO5506AC/6506AC/7506AC TT7CI21.PRI
[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Upper exit tray, Side exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with

180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes
Color: Color, Grayscale, *Auto, Twin color - 2KR, Twin color - 2KG, Twin color - 2KB, Twin color - 2KC, Twin color - 2KM, Twin color - 2KY, Twin color - 2KW
Image quality type: *Normal, Photo, Presentation, Lineart
Halftone: *Auto, Smooth, Detail
Color Balance - Cyan: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Magenta: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Yellow: FC, FD, FE, FF, *00, 01, 02, 03, 04
Color Balance - Black: FC, FD, FE, FF, *00, 01, 02, 03, 04
Sharpness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Brightness: FC, FD, FE, FF, *00, 01, 02, 03, 04
Contrast: FC, FD, FE, FF, *00, 01, 02, 03, 04
Saturation: FC, FD, FE, FF, *00, 01, 02, 03, 04
Background adjustment: FC, FD, FE, FF, *00, 01, 02, 03, 04
Pure black: Yes
Pure gray: Yes
Black overprint: Yes

[049] e-STUDIO5508A/6508A/7508A/8508A TT8PI11.PRI
[PDL]: PCL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

[050] e-STUDIO5508A/6508A/7508A/8508A TT8PI21.PRI

[PDL]: PCL
[Scripts/Languages]: ISO2 (Latin 2)
[Graphics]: Yes
[OCR]: No
[Printer-resident bar code]: No
[Paper sizes]: DIN A3, DIN A4, DIN A5, LETTER, LEGAL
[Color]: Yes
[Input trays]: Yes (See [POSS] section for details.)
[SNMP Job status feedback]: No
[POSS (Print Options for SAPScripts and Smartforms)]
* denotes the default value in the device type file
Print Mode: *Normal, Proof, Private, Hold, Anywhere
Collate: *Sort, Group, Rotated Sort
Duplex: *None, Long Edge, Short Edge
Orientation: *Portrait, Landscape
Input Tray: *Auto, Bypass Tray, Drawer 1, Drawer 2, LCF, Drawer 3, Drawer 4, External LCF
Output tray: Tray 1, *Tray 2, Exit tray
Hole punch: *None, Long Edge without Rotation, Short Edge without Rotation, Long Edge with 180 degree Rotation, Short Edge with 180 degree Rotation
Stapling: *None, Top Left, Left, Bottom Left, Top Right, Right , Bottom Right, Top, Bottom, Center Double
User login: Yes
Department code: Yes (5 digit numbers)
Project Code: Yes (63 characters)
Number of copies: 1-9999
Booklet: Yes
Font pitch: Yes

Details (Label Printers):

<Supported features>
[L001] B-EX 203dpi TTLZBI12.PRI
[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

[L002] B-EX 300dpi TTLZBI13.PRI
[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

[L003] B-EX 600dpi TTLZBI16.PRI

[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

[L004] B-SA 203dpi TTLZBI12.PRI
[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

[L005] B-SA 300dpi TTLZBI13.PRI
[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

[L006] B-SX6T TTLZBI13.PRI
[PDL]: ZPLII
[Printer driver]: LZPL
[Scripts/Languages]: ISO1 (Latin 1)
[Graphics]: Yes
[OCR]: No
[Printer-resident barcode]: Yes
[Paper sizes]: No
[Color]: No
[Input trays]: No
[SNMP Job status feedback]: No

Revision History
[05 August 2011]
- Updated device typefiles [001], [002], [003], [004], [005], [006], [007], [008] to Version 1.1.
- Fixed paper size issue in ABAP printing.

[02 April 2012]
- Added device type files [017], [018], [019], [020] (Version 1).

[20 August 2012]

- Added device type files [023], [024] (Version 1).

[18 February 2013]
- Added device type files [025], [026], [027] (Version 1).

[26 February 2013]
- Added Label Printer description and device type files [L001], [L002], [L003], [L004].

[05 March 2013]
- Changed to support LZPL driver in [L001], [L002] Label printers.

[29 March 2013]
- Added Label printer description and device type file [L003].

[17 June 2013]
- Added support for additional printer models [L004] and [L005].

[05 July 2013]
- Added new models to device type files [023] and [024]. (Version remains to be 1.)
- Added device type files [028], [029], [030], [031], [032], [033] (Version 1).

[25 July 2013]
- Added support for additional printer model [L006].

[27 February 2014]
- Added new models to device type files [012] and [014]. (Version remains to be 1.)

[04 June 2014]
- Added new models to device type files [017], [018], [019] and [020]. (Version remains to be 1.)

[26 Dec 2014]
- Added device type files [034], [035] (Version 1).

[24 Feb 2015]
- Added new models to device type files [036], [037], [038], [039] and [040]. (Version remains to be 1.)

[25 Mar 2016]
- Added new models to device type files [041] and [042]. (Version1.)

[28 Apr 2016]
- Added new models to device type files [043],[044],[045] and [046]. (Version1.)

Validity

This document is not restricted to a software component or software component version

---

References

This document is referenced by:

Customer Incident (13)

Number	Year	Title	Status	Processor	Customer Number	Customer Name
0000093458	2014	Label printing with TEC-B452 printer	Confirmed Autom.	Maguire Kenneth	0000204069	Spin Master Ltd.
0000878658	2015	No device type of Toshiba Printer - TOSH	Confirmed Autom.	Badovszky Laszlo	0000163486	Syngenta AG
0000111717	2016	Driver/Device type for printer TOSHIBA e	Confirmed	Badovszky Laszlo	0014726814	Bia Group SA
0000113739		Printer device types for not available	Confirmed		0000163221	Jabil Circuit, Inc.
0000111091		Toshiba Printer Driver Support	Confirmed Autom.	Black Aidan	0000163124	The Scotts Miracle-Gro Company

more...

SAP Notes (2)

1097990 List of Printer Vendor Wizard Notes
135894 Label printing on thermal (transfer) printers
1097990 Liste der Printer-Vendor-Wizard-Hinweise

more...

Attachments

File Name	File Size (KB)	Mime Type
TOSHIBA_TEC_Label_DevTyps.ZIP	12	application/x-zip-compressed
TOSHIBA_TEC_DevTyps.ZIP	1988	application/x-zip-compressed
TOSHIBA_TEC_DevTyps_Rev_2.zip	448	application/x-zip-compressed